

GARDEN CENTRIFUGA MULTIGIRANTI MULTI-IMPELLER CENTRIFUGAL GARDEN-PUMP

LIMITI D'IMPIEGO

- Temperatura liquido fino a 35°C
(per un uso domestico secondo EN 60335-2-41)
Temperatura max. liquido: 35°C (per altri impieghi)
- Temperatura ambiente fino a 40°C
- Altezza d'aspirazione manometrica fino a 7 mt.
- Servizio continuo

MOTORE

- Motore elettrico ad induzione a 2 poli
(n = 2850 r.p.m.)
- Isolamento Classe F
- Protezione IP 44

MATERIALI

- | | |
|---------------------|------------------|
| - Corpo pompa | Polipropilene |
| - Supporto motore | Polipropilene |
| - Girante | Noryl |
| - Diffusori | Noryl |
| - Camicia pompa | Acciaio Inox |
| - Albero motore | Acciaio Inox |
| - Tenute meccaniche | Ceramica/Grafite |

OPERATING CONDITIONS

- Liquid temperature up to 35°C
(for home use according to EN 60335-2-41)
Temperature max. liquid: 35°C (for other uses)
- Ambient temperature up to 40°C
- Total suction lift up to 7 mt.
- Continuous duty

MOTOR

- Two-Pole induction motor
(n = 2850 r.p.m.)
- Insulation Class F
- Protection IP 44

MATERIALS

- | | |
|--------------------|------------------|
| - Pump body | Moplen |
| - Motor Support | Moplen |
| - Impeller | Noryl |
| - Diffusers | Noryl |
| - Pump casing | Stainless Steel |
| - Shaft with motor | Stainless Steel |
| - Mechanical seal | Ceramic/Graphite |



TIPO - TYPE	GMP 1100/4
P1	1100 W
Voltage	230 V
Frequency	50 Hz
Ampere	4,8 A
Q max.	90 l/1'
H max.	48 m
DNM - DNA	1" - 1"
Dimensions (P x L x H)	242 x 490 x 270 mm
Weight	11,9 kg

