

SMC-3A



ELETTROPOMPA SOMMERSA MULTISTADIO ELETTRONICA ELETRONIC MULTISTAGE SUBMERSIBLE PUMP

LIMITI D'IMPIEGO

- Temperatura liquido fino a 35°C
(per un uso domestico secondo EN 60335-2-41)
Temperatura max. liquido: 35°C (per altri impieghi)
- Profondità d'immersione 12 mt.
- Partenza/ora 30 max.
- Passaggio solidi Ø 3 mm
- Livello min. d'aspirazione 60 mm

MOTORE

- Motore elettrico ad induzione a 2 poli
(n = 2850 min⁻¹)
- Protezione amperometrica a riarmo automatico incorporata
- Isolamento Classe F
- Protezione IP X8
- Cavo alimentazione 15 mt.

MATERIALI

- Corpo pompa cilindro Acciaio Inox
- Griglia Noryl
- Girante e diffusori Noryl
- Supporti Alluminio
- Albero Acciaio Inox
- Corpo motore Acciaio Inox
- Tenuta meccanica

OPERATING CONDITIONS

- Liquid temperature up to 35°C
(for home use according to EN 60335-2-41)
Temperature max. liquid: 35°C (for other uses)
- Submersion depth 12 mt.
- Start/hour 30 max
- Grain size inlet Ø 3 mm
- Min. suction level 60 mm

MOTOR

- Two-Pole induction motor
(n = 2850 min⁻¹)
- Built-in over load motor protector with automatic reset
- Insulation Class F
- Protection IP X8
- Power cable 15 mt.

MATERIALS

- External pump body Stainless Steel
- Suction strainer Noryl
- Impeller and diffusers Noryl
- Bearing brackets Aluminium
- Shaft Stainless Steel
- Motor housing Stainless Steel
- Mechanical seal

PRESSOFLUSSOSTATO INCORPORATO NELLA POMPA PRESSURE SWITCH BUILT INTO THE PUMP



SMC 900-3A

TIPO - TYPE	
P1	900 W
Voltage	230 V
Frequency	50 Hz
Ampere	3,6 A
Q max.	100 l/1'
H max.	37 m
DNM - DNA	1"
Dimensions (P x L x H)	260 x 215 x 540 mm
Weight	10,4 kg

