

ELETTROPOMPA SOMMERSA CON TRITURATORE CUTTING SUBMERSIBLE PUMPS

LIMITI D'IMPIEGO

- Temperatura liquido fino a 35°C
(per un uso domestico secondo EN 60335-2-41)
Temperatura max. liquido: 35°C (per altri impieghi)
- Profondità d'immersione 8 mt.
- Livello min. d'aspirazione 80 mm

MOTORE

- Isolamento Classe F
- Protezione IP 68
- Protettore termico
- Cavo alimentazione 10 mt.

MATERIALI

- Corpo motore Acciaio Inox
- Corpo pompa Ghisa
- Girante alta Lega di cromo
- Albero motore Acciaio Inox
- Trituratore Acciaio Inox
- Doppia tenuta meccanica Ceramica/Grafite/NBR
Silicio/Silicio/NBR

OPERATING CONDITIONS

- Liquid temperature up to 35°C
(for home use according to EN 60335-2-41)
Temperature max. liquid: 35°C (for other uses)
- Submersion depth 8 mt.
- Min. suction level 80 mm

MOTOR

- Insulation Class F
- Protection IP 68
- Thermal protector
- Power cable 10 mt.

MATERIALS

- Motor body Stainless Steel
- Pump body Cast Iron
- High impeller Chrome alloy
- Shaft with rotor Stainless Steel
- Shredder Stainless Steel
- Double mechanical seal Ceramic/Graphite/NBR
Silicon/Silicon/NBR



STS 1100

TIPO - TYPE	
P1	1100 W
Voltage	230 V
Frequency	50 Hz
Ampere	6 A
Q max.	280 l/1'
H max.	14 m
DNM - DNA	1"½
Dimensions (P x L x H)	240 x 290 x 490 mm
Weight	21,1 kg

