

ELETTROPOMPE AUTOADESCANTI IN ACCIAIO SELFPRIMING STAINLESS STEEL PUMPS

LIMITI D'IMPIEGO

- Temperatura liquido fino a 35°C
(per un uso domestico secondo EN 60335-2-41)
Temperatura max. liquido: 60°C (per altri impieghi)
- Temperatura ambiente fino a 40°C
- Altezza d'aspirazione manometrica fino a 8 mt.
- Servizio continuo

MOTORE

- Motore elettrico ad induzione a 2 poli
(n = 2850 r.p.m.)
- Isolamento Classe F
- Protezione IP 44

MATERIALI

- Corpo pompa: Acciaio Inox
- Coperchio corpo pompa: Acciaio Inox
- Supporto motore: Ghisa
- Girante: Bronzo
- Raccordi: Bronzo
- Albero motore: Acciaio Inox
- Doppio anello di tenuta

OPERATING CONDITIONS

- Liquid temperature up to 35°C
(for home use according to EN 60335-2-41)
Temperature max. liquid: 60°C (for other uses)
- Ambient temperature up to 40°C
- Total suction lift up to 8 mt.
- Continuous duty

MOTOR

- Two-Pole induction motor
(n = 2850 r.p.m.)
- Insulation Class F
- Protection IP 44

MATERIALS

- Pump body: Stainless Steel
- Pump body cover: Stainless Steel
- Motor Support: Cast Iron
- Impeller: Bronze
- Connectors: Bronze
- Shaft with motor: Stainless Steel
- Double oil seal



TIPO - TYPE	TB 20	TB 25
P1	500 W	1100 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Ampere	2,3 A	4,8 A
Q max.	25 l/1'	50 l/1'
H max.	14 m	19 m
DNM - DNA	Ø 20	Ø 25
Dimensions (P x L x H)	220 x 330 x 167 mm	220 x 330 x 167 mm
Weight	6,6 kg	11,3 kg

