TM 186/11-T

IDROPULITRICE ELETTRICA AD ACQUA FREDDA CON CARRELLO
COLD WATER ELECTRIC HIGH PRESSURE WASHER WITH TROLLEY

Caratteristiche
- Pompa a 3 pistoni in ceramica con sistema biella-manovella
- Testata in ottone
- Valvola by-pass incorporata
- Aspirazione detergente incorporata
- Dispositivo di regolazione pressione
- Ugelli con attacco rapido da 0°, 15°, 25°, 40° e detergente
- Copertura in acciaio inox per proteggere da polvere e acqua
- Interruttore di comando ON / OFF

Features
- *Triplex pump with ceramic plungers, connecting rod system*
- *Brass pump head*
- *Automatic by-pass valve*
- *Low pressure detergent suction*
- *Pressure control device*
- *Rapid coupling nozzles 0°, 15°, 25°, 40° and detergent*
- *Stainless steel cover to protect the unit from dust and water splash*
- *ON / OFF control switch*

Pressione Massima / *Max. pressure*	**186 bar / 2700 psi**		
Voltage / *Frequency*	**380 V 50 Hz**		
Portata max. / *Delivery max. (l/1')*	**11**		
N° Giri / 1' *r.p.m.*	**1450**		
Potenza / *Power (HP)*	**5,5**		
Peso / *Weight* (Kg)	**62**		
Imballo *Packaging* (mm)	**L**	**P**	**H**
	920	**670**	**600**

Standard accessories

Gun, lance and nozzles

© Speroni S.p.a., Castelnovo di Sotto (Reggio Emilia), 2025