













Type	n°	n°	n°
TT 22 MT 2011	1	2	-
TT 22 MT 3017	2	4	0 - 1

						A														
Model	lt.	Type	l/min	m ³ /h	c.f.m.	kW	hp	Volt	Amp.	r.p.m.	n°	stage n°	bar	p.s.i.	kg	L x B x H			LpA R:1m-H:1m	LwA
TT 22 MT 2011	11+11	K11	230	13,8	7,9	1,5	2	230	9	1000	2	1	10	145	69	902	730	1070	≤ 92	95
TT 22 MT 3017	11+11	K17/C	410	24,6	14,1	2,2	3	230	12	1250	2	1	10	145	77,5	902	730	1070	≤ 92	95

Compressori monostadio a cinghia

Testata bicilindrica in ghisa con valvole in acciaio inox. Motore elettrico monofase sovradimensionato a forte coppia di avviamento completo di protezione termica a riarmo manuale.

Gruppo dotato di maniglie e di due ruote, adatto a servizi in cantieri e luoghi accidentati.

Single-stage belt driven compressors

Two-cylinder cast iron head provided with stainless steel valves.

Single-phase oversized electric motor with high starting torque complete with thermal protection at manual reset.

Portable compressor provided with handles and two wheels, suitable for irregular working-places.